

Mobil Delvac lubricant recommendation for Mercedes-Benz Trucks and light commercials

Mobil Delvac – a comprehensive range of engine & gear oils you can trust

The development and performance of heavy duty and light commercial truck engines is continually evolving, to meet ever increasing demands for more power, increased unit efficiency and exacting global legislative and environmental requirements.

Real technological advances have been driven not only by **Mercedes-Benz**, as a leading truck designer and manufacturer, but by Mobil, as the engine oil specialist behind the exceptional **Mobil Delvac** range of lubricants – a brand with an impeccable pedigree stretching back to 1925.

Internationally acknowledged as a powerful partnership on the racetrack through their joint **association** with the Vodafone McLaren Mercedes Formula 1 team, Mercedes-Benz and Mobil share a commitment to **quality** and **innovation** that is appreciated by every one of their customers on the road. Not least the McLaren Mercedes technicians who are transported between the European Grand Prix circuits in the team's Mercedes-Benz Actros trucks, with engines powered and **protected** by Mobil Delvac lubricants!

Today, however far you travel from the track, Mercedes-Benz trucks can benefit from the comprehensive range of high performance synthetic and mineral Mobil Delvac lubricants and specialty products, which are formulated not only to meet key Mercedes-Benz specifications, but also a wide range of OEM and industry approvals to offer outstanding **performance** and protection in the most demanding conditions, day in day out.

Whether you are an owner operator, fleet owner or workshop manager, you can entrust your Mercedes-Benz commercial vehicle lubrication to **Mobil Delvac**.

 Mercedes-Benz



“ At my workshop, when a customer wants to discuss lubricants I ask them one simple question: would you prefer to have your vehicles in the workshop or on the road? We both know that Mobil Delvac is the right answer to that one every time! ”

R. Stuewe
Workshop Supervisor,
Commercial Vehicles Mercedes-Benz
Workshop H. Mühle/Germany

Mobil Delvac Engine Oils

Specification	Engine Oil
MB-Approval 228.51	Mobil Delvac 1 LE 5W-30 Mobil Delvac XHP LE 10W-40
MB-Approval 228.5	Mobil Delvac 1 LE 5W-30 Mobil Delvac 1 5W-40 Mobil Delvac XHP Ultra 5W-30 Mobil Delvac XHP Extra 10W-40
MB-Approval 228.31	Mobil Delvac MX ESP 15W-40 Mobil Delvac MX ESP 10W-30
MB-Approval 228.3	Mobil Delvac MX Extra 10W-40 Mobil Delvac MX ESP 15W-40 Mobil Delvac MX 15W-40
MB-Approval 228.2	Mobil Delvac 1630 Mobil Delvac 1640

Please refer to your specific OEM manual for full product recommendation listings and applicable oil drain intervals

Fuel economy potential

Low SAPS



Advanced engine and emission system protection

- Heavy Duty Diesel Engine Oil with MB-Approval 228.5 and MB-Approval 228.51
- Fully Synthetic supreme performance low ash diesel engine oil that helps extend both engine and emission system life
- Provides long drain capability and fuel economy potential for modern diesel engines, including those fitted with Diesel Particulate Filters



Ultimate engine protection and long engine life

- State-of-the-art technology to deliver exceptional performance in modern low emission engines
- Advanced formulation and viscometrics with potential to improve fuel economy and maximize oil drain intervals
- Outstanding high and low temperature protection

Low SAPS



Advanced engine and emission system protection

- Synthetic extra high performance diesel engine oil engineered to provide lubrication to low emissions engines
- Designed using high performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention, volatility control and fuel economy potential.
- Suitable for engines fitted with Diesel Particulate Filters



Superior engine protection for modern diesel engines

- Surpasses stringent engine test requirements
- Formulated to provide improved soot handling, wear and oxidation resistance
- Excellent lubrication of modern heavy-duty diesel engines, promoting long engine life

Specification	Gear Oil
MB-Approval 236.91	Mobil Delvac Synthetic ATF
MB-Approval 235.8	Mobilube 1 SHC 75W-90 Mobil Delvac Synthetic Gear Oil 75W-90
MB-Approval 235.20	Mobilube HD-A Plus 80W-90
MB-Approval 235.11	Mobiltrans MBT 75W-90
MB-Approval 235.1	Mobilube GX-A 80W
MB-Approval 235.0	Mobilube S 80W-90 Mobilube HD-A 85W-90

Mobil Delvac Synthetic Gear Oil 75W-90

Fully synthetic transmission and axle oil for vehicles operating in severe service conditions

- Excellent thermal stability and resistance to high temperature oxidation
- Outstanding protection against low speed / high torque wear
- Enhanced friction reduction properties helping to improve fuel economy potential



Mobiltrans MBT 75W-90

Fully synthetic manual transmission oil

- Formulated with an advanced additive system providing excellent thermal stability and wear resistance
- Maintains lower temperatures in the transmission compared to conventional transmission oils
- Suited for use in transmissions where lubricants are exposed to very high temperatures under full-load service

Mobil Delvac Synthetic ATF

Fully synthetic Automatic Transmission Fluid

- Engineered from an advanced additive system and meeting the Allison TES-295 specification
- Utilising an optimised, fully synthetic base oil composition containing SuperSyn
- Offers outstanding gear shifting and power transfer performance



Mobil Delvac

ExxonMobil Lubricants & Specialties
Division of ExxonMobil Petroleum & Chemical

Hermeslaan 2
1831 Machelen
Belgium

© 2009 Exxon Mobil Corporation

The Mobil Delvac and ExxonMobil logotypes are registered trademarks of Exxon Mobil Corporation or one of its subsidiaries. The term "ExxonMobil" is used for convenience only and could refer to Exxon Mobil Corporation or one of its affiliates as the case may be. Other logotypes and trademarks are the property of the respective owners.

Mercedes-Benz and the Mercedes-Benz logo are registered trademarks of Daimler AG.

www.mobildelvac.com